



Pochette Up/Down Led

Designed by Rodolfo Dordoni, 2003



22W - 1744lm - 2700K - CRI> 90

Wall lamp providing direct/indirect light. Pressure die-cast Zamak alloy structure, matte gray, shiny white or chrome plated finish. Molded steel, galvanized white wall attachment containing the wall attachment system as well as the electrical devices.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

145 mm 197 mm

Main specifications

EAN	8059607024249	
Mounting	Wall	
Environments	Indoor dry location	
Light source type	LED	
Light sources included	Yes	
LED type	LED Module	
Power (W)	22	
Lumen Output (lm)	1744	

Physical

Colour	White
Length (mm)	197
Net weight (kg)	1.7
Package height (mm)	135
Package width (mm)	265
Package length (mm)	180
Package volume (m3)	0.01
IP internal	20

Download

Mounting instructions



Photometric Files

LDT / IES



Technical Drawings

2D	$\overline{7}$	ZIP
3D	<u>\psi}</u>	ZIP

















Schematic light drawing



Beam	Angle:	107°
h(m)	E(lx)	D(m)
1	659	2.74
2	165	5.47
3	73	8.21
4	41	10.95
5	26	13.68

Photometric

Light distribution	Asymmetric
CCT (K)	2700
CRI>	90
Extreme cut off	No

Electrical

Insulation class	I	
Frequency (Hz)	50/60	
Main voltage (Vac)	220-240	
Power supply	Integrated	
Dimmable	Yes	
Power supply type	Dimmable 1-10V	
Dimming interface	Remote Dimmable (Dimmer Not Included)	
Batteries inside	No	

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E




Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Spare Parts



- 01. Up transparent diffuser RF25606
- D2. Led power supply RF25062





RF25606 RF25062

Up transparent diffuser Led power supply