




Skygarden 1

Designed by Marcel Wanders, Marcel Wanders studio, 2007



Halogen - 150W

Suspension luminaire providing diffused lighting. Hemispherical, mechanically-processed cast plaster diffuser, painted white inside. Outer finish: rust, glossy black, glossy white or matte gold. Plaster diffuser support in die-cast aluminum alloy, liquid-painted white. Molded upper bushing in die-cast, polished aluminum alloy, protected with transparent paint on the entire visible part. Upper cable gland and blocking ring nut in black injection-molded PC (polycarbonate). Shaped, galvanized adjustment screws. Transparent, injection-molded, upper and lower silicone shock absorbers. Lamp holder and fixing support in black injection-molded PPS (polyphenylene sulfide). Flashed and blown opal glass diffuser. Molded fixing ring nut in die-cast aluminum alloy with alodine plating. Skygarden 1 frieze in photo-etched and mechanically drawn AISI 304 steel. Molded and galvanized steel ceiling attachment Gray, injection-molded PA6 (Nylon) rose.



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Download Mounting instructions	⊥ PDF
Photometric Files LDT/IES	⊥ LDT
Technical Drawings	5
2D	₹ ZIP
2D 3D	₹ ZIP

Main specifications

EAN	8059607012741				
Mounting	Suspension				
Environments	Indoor dry location				
Light source type	Bulb				
Light sources included	No				
Lamp category	Halogen				
Lamp holders	E27				
Ilcos	HSGS				
Number of lamps	1				
Power (W)	150				

Physical

Colour	Glossy White			
Length (mm)	600			
Cord colour	Clear			
Cord length (mm)	2700			
Canopy colour	White			
Canopy length/diameter (mm)	146			
Canopy height (mm)	36			
Net weight (kg)	13			
Package height (mm)	435			
Package width (mm)	730			
Package length (mm)	730			
Package volume (m3)	0.23			
IP internal	20			

Schematic light drawing



 Beam Angle:
 118°

 h(m)
 E(lx)
 D(m)

 1
 416
 3.36

 2
 104
 6.72

 3
 46
 10.08

 4
 26
 13.44

 5
 17
 16.79

_										
Ρ	n	റ	t	\sim	m	ገ	21	М	٦.	$\boldsymbol{\Gamma}$
		u	u	v			_	LI	- 1	L

Light distribution	Symmetric
Extreme cut off	No

Electrical

Insulation class	I		
Frequency (Hz)	50/60		
Main voltage (Vac)	220-250		
Dimmable	Yes		
Dimming interface	Remote Dimmable (Dimmer Not Included)		
Batteries inside	No		

https://professional.flos.com/en/global/product/skygarden-1-f0001009/

F0001009




NOT INCLUDED

RF29388

LED T46 Lamp E27 20W 2700K Dimmable

Spare Parts



White rose assembly RA3690209
 Skygarden 1 glass diffuser RF6410100
 Kit of 5 or rings RF05382





00000

RA3690209

RF6410100

RF05382

White rose assembly

Skygarden 1 glass diffuser

Kit of 5 or rings

https://professional.flos.com/en/global/product/skygarden-1-f0001009/